



GB 98/03728

The
Patent
Office

PCT/GB 98/03728

11 DECEMBER 1998

09/581457

INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP9 1RH

S

REGD 22 JAN 1999

WIPC PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

G D Court.
23 DEC 1998



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

J00040374GB

2. Patent application number

(The Patent Office will fill in this part)

9726362.8

12 DEC 1997

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ORANGE PERSONAL COMMUNICATIONS SERVICES LIMITED
St James Court
Great Park Road
Almondsbury
Bristol BS12 4QJ
United Kingdom

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

6649032003

4. Title of the invention

MOBILE COMMUNICATIONS

5. Name of your agent (if you have one)

R.G.C. Jenkins & Co

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

26 Caxton Street
London
SW1H 0RJ
United Kingdom

Patents ADP number (if you know it)

950001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes.

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 15

Claim(s) 5

Abstract 1

Drawing(s) 4 + 4

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.
- Signature *R.G.C. Jenkins & Co* Date 12 December, 1997
R.G.C. Jenkins & Co
12. Name and daytime telephone number of person to contact in the United Kingdom Mr Jerome Spaargaren
0171 931 7141

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

MOBILE COMMUNICATIONS

This invention relates to mobile communications, in particular to the transmission of radio resource signalling reports from mobile stations in a cellular communications system, and to the handling thereof within the system.

In known mobile communications systems, such as the GSM (Global System for Mobile communications), it is known for mobile stations to take radio link measurements during progress of a call, and to report these measurements to the serving base station. The base station uses these downlink measurement reports in order to determine when a handover is required.

Handover is initiated by the base station using radio sub-system criteria (signal strength level, link quality, link distance, etc) as well as network directed criteria (e.g. current traffic loading per cell, maintenance requests, etc).

In addition, current networks such as GSM networks include a mobile switching centre (MSC), a second generation component in the form of a large, central switch.

Third generation systems are proposed in which various levels of service are provided and in which the MSC functionality is provided in a distributed processing environment, rather than in the form of a central switch.

It would be desirable to provide a more flexible and sophisticated approach to radio resource allocation. It would also be desirable to provide for the re-use of existing mobile network elements, in particular base stations, whilst providing enhanced radio resource signalling functionalities.

5 In accordance with one aspect of the invention there is provided a method of transmitting signalling reports from a mobile station to a serving base station in a cellular communications system comprising a network infrastructure and a plurality of base stations connected thereto, said method comprising transmitting radio measurement reports intended for use by said
10 serving base station to allocate a radio resource to said mobile station, and transmitting a radio resource signalling report intended for use by a service node in said network infrastructure to allocate a radio resource to said mobile station.

 This aspect of the invention allows radio resources to be allocated by
15 the serving base station when appropriate, whilst also allowing radio resources to be allocated by a service node higher in the network hierarchy in other circumstances. This prevents excessive signalling load in the network, whilst allowing additional parameters not available to the base station to be taken into account when allocating radio resources in these other circumstances.

20 In accordance with a further aspect of the invention there is provided a method of transmitting signalling reports from a mobile station to a cellular communications system comprising a plurality of base stations including a

base station serving said mobile station via a radio link, said method comprising encapsulating a radio resource signalling report before transmission over said radio link, such as to prevent said serving base station from intercepting said radio resource signalling data.

5 This aspect of the invention provides a method whereby radio resource signalling reports may be transmitted transparently through the serving base station, and onwards to further elements in the system. The encapsulation is preferably by means of a mobile-originating SMS message, which allows existing radio interface functionality to be used to conceal the radio resource
10 signalling report from the base station.

 In accordance with a yet further aspect of the invention there is provided a cellular communications system comprising a plurality of base stations for conducting communications with mobile stations via a radio interface, and a service node for collecting radio resource signalling reports
15 generated by mobile stations when in connected mode in said system, said system comprising means for receiving said reports from said plurality of base stations and for routing same to said service node.

 This aspect of the invention provides for the collection and use of radio resource-related data at the service node, to allow radio resource
20 allocation to be conducted by said service node on the basis of such radio resource signalling reports. For example, the service node may perform handover decision algorithms on the basis of the data contained in the radio

resource signalling reports, along with other data such as data specifying bandwidth, cost and/or quality of service requirements for the mobile stations.

Preferred embodiments of the invention will now be described with reference to the accompanying drawings, wherein:

5 Figure 1 is a schematic block diagram of a prior art mobile communications network;

 Figure 2 is a schematic block diagram of a mobile station for use in relation to the present invention;

 Figure 3 is a schematic block diagram of a mobile communications
10 system in accordance with the present invention; and

 Figure 4 is a schematic diagram illustrating functionality provided in accordance with the present invention.

 A GSM network, referred to as a public land mobile network (PLMN), is schematically illustrated in Figure 1. This is in itself known and will not be
15 described in detail. A mobile switching centre (MSC) 2 is connected via communication links to a number of base station controller (BSCs) 4. The BSCs 4 are dispersed geographically across areas served by the mobile switching centre 2. Each BSC 4 controls one or more base transceiver stations (BTSs) 6 located remote from, and connected by further
20 communication links to, the BSC. Each BTS 6 transmits radio signals to, and receives radio signals from, mobile stations 8 which are in an area served by that BTS. That area is referred to as a "cell". A GSM network is provided

with a large number of such cells, which are ideally contiguous to provide continuous coverage over the whole network territory. Indeed, a number of GSM networks may operate in the same areas to provide overlapping coverage.

5 The mobile switching centre 2 is also connected via communications links to other mobile switching centres in the remainder of the mobile communications network 10, and to other networks such as a public service telephone network (PSTN), which is not illustrated. The mobile switching centre 2 is provided with a home location register (HLR) 12 which is a
10 database storing subscriber authentication data including the international mobile subscriber identities (IMSI) which are unique to each mobile station 8. An IMSI consists of a mobile country code (3 decimal digits), a mobile network code (2 decimal digits) and a mobile subscriber code (up to 10 decimal digits) identifying a subscriber within a particular network. The IMSI
15 is also stored in the mobile station in a subscriber identity module (SIM) (to be described below) along with other subscriber-specific information.

 The mobile switching centre is also provided with a visitor location register (VLR), not shown, which is a database temporarily storing subscriber authentication data for mobile stations active in its area.

20 In addition, the MSC is connected to a short message centre (SMC) 13 for handling the transfer of short messages addressed to and from mobile stations within the network. The short message service (SMS) is a point-to-

point message service as specified in GSM Technical Specification 03.40. A user of a mobile station 8 may generate a mobile-originating SMS message by input to a Man Machine Interface (MMI) (e.g. a keypad) of the mobile station 8, and transmit the message, along with a destination address, to the servicing

5 BTS 6. The message is forwarded transparently to the MSC 2, which directs the message on to the SMC 13. The SMC 13 generally holds the message and handles the onward transmission to the terminating station corresponding to the directory number specified in the SMS message by the user of the mobile station 8.

10 When switched on within coverage of the mobile network, the mobile station has two possible modes, namely idle mode and connected mode. Both of these are described in GSM Technical Specification 05.08.

In idle mode, the mobile station 8 measures radio sub-system downlink performance and signal strengths received from surrounding cells.

15 The mobile station 8 selects a preferred cell according to a cell selection algorithm, and informs the network via a signalling channel of its selection. Occasionally, when the mobile station moves to a new cell site, the mobile station transmits a location update to the mobile network via a signalling channel.

20 When in connected mode, the mobile station 8 initiates a call establishment procedure and is allotted a dedicated channel (a "connection") for the transfer of voice and/or data traffic over the radio interface. The

dedicated channel includes a main traffic channel (TCH) for carrying the voice or data traffic, and a low-rate signalling channel (the Slow Associated Control Channel, SACCH). When in connected mode, the mobile station continuously performs radio measurements from the serving cell BTS and from neighbouring cell BTSs. These measurements are regularly reported to the serving cell BTS on the SACCH. The mobile station can report measurements relating to a number of candidate target cells in addition to the measurements relating to the serving cell. These measurements allow the serving BSC to decide when and whereto the handover of a given mobile station in connected mode is to be initiated. The BSC intercepts the measurement reports generated by the mobile station and sent on the SACCH part of the dedicated channel.

It is also possible for the mobile station to send, and receive, short messages (SMS messages) when in connected mode. Such short messages are then sent over the SACCH part of the dedicated channel assigned to the mobile station, and are differentiated from signalling (in particular, the measurement reporting signalling) transmitted over the SACCH by means of a different link identifier (SAPI). The signalling messages are allotted SAPI 0, whilst short messages are allotted SAPI 3. The mobile-originating short messages are not intercepted by the BSC, but are transmitted to the MSC, which generally directs the short messages using the destination address in the short message header to the SMC 14.

Figure 3 schematically illustrates an embodiment of the present invention, in which re-use of GSM-type BSCs 4 and BTSs 6, as well as at least part of the GSM radio interface, is possible, whilst a distributed processing network infrastructure, using intelligent network (IN)-type
5 functionality, replaces the prior art elements associated with and including the MSC 2.

In the arrangement of this embodiment of the invention, the BSCs 4 of one connectivity provider are connected to a first service access node 100, whereas those of a second connectivity provider are connected to a second
10 service access node 102.

Each of the service access nodes 100, 102 have connections to service provision, mobility management, switching and other connection elements, not illustrated. The service access nodes 100, 102 are interconnected using an ATM link 104.

15 In addition, a service node 106 is connected to each of the service access nodes 100, 102, using signalling links. The service node 106 is provided with a database 108. The service node 106 is adapted to perform predefined handover algorithms in order to make handover decisions based on parameters stored in database 108.

20 The data stored in database 108 includes, for all currently-active subscribers in each of the areas covered by the two connectivity providers, data relating to the following:

1. Radio link quality. Radio link measurement is performed for the current downlink in the mobile station 8, and for the current uplink in the serving BTS 6. The measurements include, for example, bit error rate, delay, delay jitter, change in quality of service, link loss probability and the time
5 before link loss.

2. A list of target radio access nodes. This is needed to determine the cell to which the radio link should be handed over to. The list is accompanied by information regarding the node capacity and node occupation.

10 3. Personal subscriber profile and service information, including bandwidth requirements, quality of service requirements, access rights, priority and preference lists, environment selection, provider selection, etc.

4. Operational criteria, which include all the quasi-static parameters (congestion and load control related parameters) required to
15 identify the need for handover.

The mobile station 8 performs radio link measurements for both the serving cell and the neighbouring cells during connected mode. In addition to the mobile station being adapted for transmitting these measurements in a conventional GSM-type measurement report as signalling on the SACCH to
20 the serving BTS, the mobile station is adapted to encapsulate radio resource measurement reports short messages which are addressed to the service node 106. The mobile-originating short message is constructed by the mobile

station 8 using an originating address/destination address header combination identifying to the service access node 100 that the short message contains radio link measurement data, instead of a user-defined short message. This ensures that the service access node 100 transmits the measurement report short message to the service node 106, rather than the short message centre (not shown) provided in the intelligent network functionality.

Furthermore, since the measurement report is encapsulated as a short message, the measurement report is not intercepted by the serving BTS/BSC, which would otherwise be the case if the measurement report were transmitted as normal signalling on the SACCH. This takes the decision to attempt a handover out of the sole control of the BSC, and allows handover decisions to be made in the service node 106.

During connected mode, the transmission of measurement reports as normal signalling on the SACCH to the serving BTS/BSC generally occurs continually, such that normal handover decisions may then be made by the BSC 4.

When the mobile station has particular requirements e.g. bandwidth and/or quality of service, the SMS-encapsulated measurement reports are transmitted by the mobile station instead of, or in addition to, the normal signalling measurement reports, so as to allow radio resource allocation decisions to be made by the service node 106.

The mobile station may be adapted to automatically transmit an SMS-encapsulated measurement report on its own initiative when predetermined service requirement criteria are met.

Alternatively or in addition, the mobile station may transmit an SMS-
5 encapsulated measurement report on receipt of a request from the service node 106. The service node transmits such a request when other predetermined service requirement criteria are met.

The service node 106 can thus, on receipt of a measurement report, make handover decisions based on parameters not available to the individual
10 BSCs, for example the personal profile and service information.

Figure 4 schematically illustrates a situation in which handover between two connectivity providers is possible, and in which the mobile terminal reports basic measurement data to the service node database 108. Mobile terminal 8 is in the vicinity of seven BTSs 6 having frequency channel
15 numbers 835, 822, 788, 821, 780, 800 and 830 respectively. The signal strength measurements (between -106dBm and -80dBm) made by the mobile terminal are converted into corresponding quality index numbers (between 0 and 26), and these quality index numbers are encapsulated, along with the Base Station Identification codes and frequency channel numbers, in a
20 mobile-originating SMS message which is transmitted automatically on the SACCH by the mobile terminal 8 to the serving BTS 6. The message is

transmitted transparently onwards through the serving BSC 4, into the network, represented by box 110, and into the service node database 108.

The measurement reporting data encapsulated in the short messages is thus sufficient to precisely identify base stations that are visible to the mobile station 8 by means of the base station identification codes, and their associated signal strengths. The service node 106 may decide, on executing a handover algorithm using this measurement data, that a handover should be executed from the serving BTS (frequency channel number 788) belonging to one connectivity provider to a second BTS (frequency channel number 800) belonging to a second connectivity provider. The handover, under instruction from the service node 106, is then performed in the network in accordance with known handover procedures.

A decision to handover a connection may be made based on criteria such as bandwidth (in the case where the mobile station has multiple bandwidth capabilities), quality of service and/or cost associated with each of the different access nodes provided by the connectivity providers. The SMS message may include data relating to the current requirements of the handset and/or the subscriber. For example, the SMS message may include identifiers for preferred connection providers, bandwidth requirements, cost limits, hardware and software version numbers of the handset, etc.

In the example described in relation to Figure 4, the measurement reports encapsulated in the SMS message contained only radio quality index

numbers for each of the BTSs in the vicinity of the mobile station. It is envisaged that other parameters useful for performing handover decisions could also, or alternatively, be encapsulated in the SMS message. For example, the data may include, for the serving cell, the time slot number, the
5 base station colour code, the global cell ID, the receive quality, the receive signal level and/or the number of neighbour cells. Similar data could be provided for each of the neighbour cells, subject to optimisation to minimise signalling load within the network.

A service node is provided in a mobile communications network
10 which collects radio link measurement reports which are transmitted to the service node by mobile stations. The mobile stations transmit the measurement reports in encapsulated form, namely in the form of SMS messages, in order to prevent the interception of the measurement report by the serving base station.

15 The service node is able to perform handover decision algorithms using the measurement reports collected from the mobile stations in order to determine appropriate radio access nodes to be allocated to the mobile stations.

It is to be mentioned that handover decisions made by the service node
20 106 need not be initiated only by the service node 106 on receipt of the SMS-encapsulated reports. A handover request may be directed by the mobile station 8 to the service node 106. In this case, when the mobile station

initiates the handover request, it encapsulates a measurement report as an SMS message directed at the service node 106, which performs the handover decision algorithm to determine which radio access node would best serve the mobile station.

5 In the above-described embodiments, the measurement report is encapsulated as a mobile-originating SMS message, to ensure that the measurement report is not intercepted by the serving BTS/BSC. It is envisaged that other modes of encapsulation would also be possible in order to prevent interception of a measurement report by the serving BTS/BSC. For
10 example, the measurement report may be carried using an envelope and/or a message discriminator recognized at the serving BTS/BSC such that the serving BTS/BSC acts as a transparent relay for the measurement report and allowing the measurement report to reach the service node 106. A unique envelope definition could be provided for the encapsulation of such a
15 measurement report which is recognised by the BTS/BSC interface in the network and by the service access node(s), such that it is directed to the service node 106.

 Furthermore, the present invention is not limited to the transmission of measurement reports to the service node 106. Alternative radio resource
20 signalling data, for example only user preferences, or user requirements or handover requests alone, could also be encapsulated and sent in a similar manner.

Although a particular mobile station has been described above as an example, the mobile stations may be any or all of:

personal digital assistants,
cellular telephones,
5 satellite telephones,
video phones,
facsimiles,
portable personal computers, etc.

10 It should be mentioned that the present invention is not limited to arrangements in which GSM-type BSCs and BTSs are re-used. Other cellular network arrangements, in particular third generation systems, would also benefit from use of the present invention.

It is envisaged that further variations and modifications may be employed without departing from the scope of the present invention.

CLAIMS

1. A method of transmitting signalling reports from a mobile station to a serving base station in a cellular communications system comprising a network infrastructure and a plurality of base stations connected thereto, said method comprising transmitting radio measurement reports intended for use by said serving base station to allocate a radio resource to said mobile station, and transmitting a radio resource signalling report intended for use by a service node in said network infrastructure to allocate a radio resource to said mobile station.

2. A method of transmitting signalling reports from a mobile station to a cellular communications system comprising a plurality of base stations including a base station serving said mobile station via a radio link, said method comprising encapsulating a radio resource signalling report before transmission over said radio link, such as to prevent said serving base station from intercepting said radio resource signalling data.

3. A method according to claim 1 or 2, comprising encapsulating said radio resource signalling reports in the form of a mobile-originating SMS message.

4. A method according to claim 1, 2 or 3, comprising transmitting said radio resource signalling report during a dedicated channel traffic connection for said mobile station.

5 5. A method according to any preceding claim, said radio resource signalling report comprising downlink quality data measured for said serving base station.

10 6. A method according to any preceding claim, said radio resource signalling report comprising signal strength data measured for neighbouring cell base stations.

15 7. A method according to any preceding claim, said radio resource signalling data comprising data specifying the current requirements of said mobile station.

8. A method according to claim 7, said current requirements comprising bandwidth, cost and/or quality of service requirements.

20 9. A method according to any preceding claim, comprising transmitting said radio resource signalling report in response to a request from said cellular communications system.

10. A method according to any of claims 1 to 8, comprising transmitting said radio resource signalling report in response to a request from said user.

5

11. A method of transmitting radio resource signalling reports from a mobile station in a cellular communications system, comprising transmitting said reports in the form of mobile-originating SMS messages.

10

12. A mobile station adapted to perform the method of any of claims 1 to 11.

15

13. A cellular communications system comprising a plurality of base stations for conducting communications with mobile stations via a radio interface, and a service node for collecting radio resource signalling reports generated by mobile stations when in connected mode in said system, said system comprising means for receiving said reports from said plurality of base stations and for routing same to said service node.

20

14. A system according to claim 13, wherein said radio resource signalling reports comprise downlink quality data measured by said mobile

stations and/or neighbour cell signal strength data measured by said mobile stations.

15. A system according to claim 13 or 14, wherein said radio
5 resource signalling reports comprise data specifying bandwidth, cost and/or
quality of service requirements for said mobile stations.

16. A system according to claim 13, 14 or 15, wherein said service
node is adapted to select a radio access nodes to be allocated to said mobile
10 stations or the basis of said reports.

17. A system according to claim 16, wherein said service node is
adapted to select radio access nodes to be allocated to said mobile stations on
the basis of individual bandwidth, quality of service and/or cost requirements
15 for said mobile stations.

18. A system according to any of claims 13 to 17, wherein said
base stations are adapted to select radio resources to be allocated to said
mobile stations on the basis of radio measurement reports received from said
20 mobile stations.

19. A system according to any of claims 13 to 18, wherein said system is adapted to transmit a request for said one of said reports to one of said mobile stations in response to a change in the service conditions for said one mobile station.

5

20. A system according to any of claims 13 to 19, comprising means for extracting said radio resource signalling reports from SMS messages received from said mobile stations.

ABSTRACT

A service node is provided in a mobile communications network which collects radio link measurement reports which are transmitted to the service node by mobile stations. The mobile stations transmit the measurement reports in encapsulated form, namely in the form of SMS messages, in order to prevent the interception of the measurement report by the serving base station.

The service node is able to perform handover decision algorithms using the measurement reports collected from the mobile stations in order to determine appropriate radio access nodes to be allocated to the mobile stations.

THIS PAGE BLANK (USPTO)




FIG. 1 (PRIOR ART)

THIS PAGE BLANK (USPTO)




FIG. 2

THIS PAGE BLANK (USPTO)




FIG. 3

THIS PAGE BLANK (USPTO)

ACT/9898/03728

11/12/98

RSC JENKINS & CO

THIS PAGE BLANK (USPTO)